

Online Bin Packing with Advice^{*}

Joan Boyar¹, Shahin Kamali², Kim S. Larsen¹ Alejandro López-Ortiz²

¹ University of Southern Denmark, Denmark

² University of Waterloo, Canada.

Abstract. We consider the online bin packing problem under the advice complexity model where the “online constraint” is relaxed and an algorithm receives partial information about the future requests. We provide tight upper and lower bounds for the amount of advice an algorithm needs to achieve an optimal packing. In a theoretical setting in which there is no restriction on items sizes, we show that $n \log \text{OPT} - o(n \log \text{OPT})$ bits of advice are necessary to achieve an optimal packing, where n is the length of the sequence and OPT is the cost of an optimal packing. This matches the natural upper bound of $n \log \text{OPT}$ bits up to additive lower order terms and is in that sense optimal. In a more practical setting in which there are a constant number of m distinct items, we show that $(m - 3) \log n - O(1)$ bits of advice are necessary and $m \log n$ bits are sufficient to achieve an optimal packing. We also introduce an algorithm that, when provided with $\log n$ bits of advice, achieves a competitive ratio of $3/2$ for the general problem. This algorithm is simple and is expected to find real-world applications. We introduce another algorithm that receives $2n + o(n)$ bits of advice and achieves a competitive ratio of $4/3$. Finally, we provide a lower bound argument that implies that advice of linear size is required for an algorithm to achieve a competitive ratio better than $5/4$.

1 Introduction

In the classical one-dimensional bin packing problem the goal is to pack a given sequence of *items* into a minimum number of *bins* with fixed and equal capacities. For convenience, it is assumed that items sizes are in the range $(0, 1]$ and the capacities of bins are 1. In the *online* version of the problem, the items are revealed one by one, and an algorithm must pack each item without any knowledge about future items. The decisions of an online algorithm are irrevocable, i.e., it is not possible to move an item from one bin to another after it is *placed* in a bin.

The online bin packing problem has many applications in practice, from loading trucks subject to weight limitations to creating file backups in removable media [8]. Heuristics that have been proposed for the problem include First-Fit (FF), Best-Fit (BF), and the Harmonic-based class of algorithms. FF keeps a list of bins in the order they are opened, places an item in the first bin that has enough space, and opens a new bin if necessary. BF performs similarly to FF, except that the bins are ordered in increasing

^{*} The work of the first and third author was partially supported by the Danish Council for Independent Research, Natural Sciences, and the work was carried out while these authors were visiting the University of Waterloo.

order of their remaining capacity. Harmonic-based algorithms are based on the idea of packing items of similar sizes together in a bin.

Similar to other online problems, the standard measure for comparing bin packing algorithms is competitive analysis. Under competitive analysis, the performance of an algorithm $\mathbb{A}$ is compared to that of OPT , which is the optimal offline algorithm. More precisely, the competitive ratio of an algorithm $\mathbb{A}$ is the asymptotically maximum ratio of the cost of $\mathbb{A}$ to that of OPT for serving the same sequence σ . FF and BF have the same competitive ratio of 1.7, while the best Harmonic-based algorithm has a competitive ratio of at most 1.58889 [21]. It is also known that no online algorithm can have a competitive ratio better than 1.54037 [3].

The difference between the conditions for the online algorithms versus the optimal offline algorithm gives rise to some problems. In many cases, it is not possible to separate online algorithms that have equally bad competitive ratios because of the online constraint versus the optimal algorithm’s powerful knowledge of the entire future. Moreover, the total lack of information about the future is unrealistic in many real-world scenarios [11]. A natural approach for addressing this issue is to relax the problem by providing extra information about the input sequence. For the online bin packing problem, such relaxations have been studied in the contexts of *lookahead*, in which the online algorithm can look at the items arriving in the near future [14], and *closed bin packing*, in which the length of the request sequence is known to the online algorithm [1]. In both cases, the average performance of the online algorithm improves, compared to the online algorithms with no information about the future.

The advice complexity model for online algorithms is a more general framework under which the “no knowledge assumption” behind online algorithms is relaxed, and the algorithm receives some bits of *advice* about the future requests. The advice can be any information about the input sequence and is generated by an offline oracle which has unbounded computational power. Provided with the appropriate advice, the online algorithms are expected to achieve improved competitive ratios. The advice model has received significant attention since its introduction [11,6,16,5,19,20,7,15,12,9].

In this paper, we study the advice complexity of the online bin packing problem. Our interest in studying the problem under this setting is mostly theoretical. Nevertheless, in many practical scenarios, it can be justified to allow a fast offline oracle to take a “quick look” at the input sequence and send some advice to the online algorithm. For example, assume we need to load trucks with items of different weights stored in a warehouse. Because of the large number of items, there is a bottleneck in measuring and storing the weight of all items. So the problem has an online nature. However, it is possible to take a quick look and count, for example, the number of items which are heavier than $1/2$ and lighter than $2/3$ (of the weight capacity of a truck). We show that this form of advice can be used to achieve an algorithm which outperforms all online algorithm.

1.1 Model

In the last few years, slightly different models of advice complexity have been proposed for online problems. All these models assume that there is an offline oracle with infinite computational power, which provides the online algorithm with some bits of advice. How these bits of advice are given to the algorithm is the source of difference between

the models. In the first model, presented in [10], an online algorithm poses a series of questions which are answered by the offline oracle in *blocks of answers*. The total size of the answers, measured in the number of bits, defines the advice complexity. The problem with this model is that a lot of information can be encoded in the individual length of each block. To address this issue, another model is proposed in [11] which assumes that online algorithms receive a fixed number of bits of advice per request. We call this model the *advice-with-request model*. This model is studied for problems, such as metrical task systems and k -server, and the results tend to use more than a constant number of bits of advice per request [11,20]. Nevertheless, there are many online problems for which a sublinear and even a constant number of bits of advice in total is sufficient to achieve good competitive ratios. For example, it is easy to see that for the ski-rental problem [17], one bit of advice suffices, and for the secretary problem [13], $\log n$ bits of advice are sufficient to achieve optimal solutions³. However, under the advice-with-request model, the possibility of sending a sublinear number of advice bits to the algorithm is not well defined. In [6,5] another model of advice complexity is presented which assumes that the online algorithm has access to an *advice tape*, written by the offline oracle. At any time step, the algorithm may refer to the tape and read any number of advice bits. The advice complexity is the number of bits on the tape accessed by the algorithm. As mentioned in [5], this *advice-on-tape model* can be used to simulate the advice-with-request model, and the lower bounds under this model directly apply to the other model. Since its introduction, the advice-on-tape model has been used to analyze the advice complexity of many problems including paging [6,16,19], disjoint path allocation [6], job shop scheduling [6,19], k -server [5], knapsack [7], bipartite graph coloring [15], online coloring of paths [12], online set cover [18,4], online maximum clique [4], and graph exploration [9].

Regarding notation, we use $\mathbb{A}(\sigma)$ to denote the costs of $\mathbb{A}$ for packing a request sequence σ . When σ follows from the context, we simply use $\mathbb{A}$ to denote this cost. We use similar notation for all algorithms, including OPT.

We consider the bin packing problem under the advice-on-tape model, which is formally defined as follows, based on the definition of the advice model in [5]:

Definition 1. *In the online bin packing problem with advice, the input is a sequence of items $\sigma = \langle x_1, \dots, x_n \rangle$, revealed to the algorithm in an online manner ($0 < x_i \leq 1$). The goal is to pack these items in the minimum number of bins of unit size. At time step t , an online algorithm should pack item x_t into a bin. The decision of the algorithm to select the target bin is a function of $\Phi, x_1, \dots, x_{t-1}$, where Φ is the content of the advice tape. An algorithm $\mathbb{A}$ with advice tape Φ is c -competitive with advice complexity $s(n)$ if there exists a constant c_0 such that, for every n and for each input sequence σ of length at most n , there exists some Φ such that $\mathbb{A}(\sigma) \leq c \cdot \text{OPT}(\sigma) + c_0$, and at most the first $s(n)$ bits of the tape have been accessed by the algorithm. An algorithm $\mathbb{A}$ is optimal if $\mathbb{A}(\sigma) = \text{OPT}(\sigma)$.*

³ In this paper we use $\log n$ to denote $\log_2(n)$.

1.2 Contribution

We answer different questions about the advice complexity of the online bin packing problem. First, we study how many bits of advice are required to achieve an optimal solution. We consider two different settings of the problem to answer this question. Under a *theoretical setting* in which there is no restriction on the number of distinct items or their sizes, we show that $n \log \text{OPT}$ bits of advice are sufficient to achieve an optimal solution. We also prove that at least $(n - 2 \text{OPT}) \log \text{OPT}$ bits of advice are required to achieve an optimal solution. Thus, $\Theta(n \log \text{OPT})$ bits are necessary and sufficient to achieve an optimal solution.

In a more practical setting in which there are m distinct items in the sequence, we prove that at least $(m - 3) \log n - 2m \log m$ bits of advice are required to achieve an optimal solution. If m is a constant, there is an online algorithm that receives $m \log n$ bits of advice and achieves an optimal solution. Hence, the lower and upper bound match for this setting. We also show that, even if m is not a constant, if all items are larger than a fixed small ε , there is an online algorithm that receives $m \log n$ bits of advice and achieves a competitive ratio of $1 + \varepsilon$. So, $\Theta(m \log n)$ bits are sufficient to achieve an almost optimal solution in this setting, while the same number of bits are required to achieve an optimal solution.

We also study a relevant question that asks how many bits of advice are required to perform strictly better than all online algorithms. We answer this question by providing an algorithm which receives $\log n$ bits of advice and achieves a competitive ratio of 1.5. It is known that any online bin packing algorithm has a competitive ratio of at least 1.54037 [3]. Hence, our algorithm outperforms all online algorithms. Both the offline algorithm that generates the advice and the online algorithm that packs the items are simple and fast. We expect that this algorithm will find applications in many real-world scenarios.

Moreover, we show that a linear number of bits of advice are sufficient to achieve a competitive ratio of $4/3 + \varepsilon$. More precisely, we introduce an algorithm that receives $2n + o(n)$ bits of advice and achieves a competitive ratio of $4/3 + \varepsilon$, for any fixed value of ε . We also prove a lower bound that implies that a linear number of bits of advice are required to achieve a competitive ratio of $5/4 - \delta$ for any fixed value of δ .

2 Optimal Algorithms with Advice

In this section we study the amount of advice required to achieve an optimal solution. We first investigate the theoretical setting in which there is no restriction on the number of distinct items or on their sizes. Later we study a more practical setting with meaningful restrictions, which are justifiable in most real-world applications.

2.1 A Theoretical Setting

We allow up to n distinct item sizes in the sequence, and their sizes can be arbitrarily small. We first observe that there is a very simple algorithm that receives $n \log \text{OPT}$ bits of advice and achieves an optimal solution.

Theorem 1. *To achieve an optimal packing for a sequence of size n and optimal cost OPT , it is sufficient to receive $n \log \text{OPT}$ bits of advice.*

Proof. Consider an offline oracle that knows an optimal packing (note that such an oracle has unbounded computational power). This oracle simply writes on the advice tape, for each item x , the index of the bin in an optimal packing that x is placed in. This requires $\log \text{OPT}$ bits of advice per item which sums up to $n \log \text{OPT}$ bits of advice. To pack any item x , the online algorithm simply reads the index of the bin that x should be placed in and packs x accordingly. $\square$

The above algorithm looks naive, and one might think that an optimal solution using a significantly smaller number of bits of advice should exist. In what follows, we prove that this is not the case, and indeed we need at least $(n - 2 \text{OPT}) \log \text{OPT}$ bits of advice to achieve an optimal packing.

Theorem 2. *To achieve an optimal packing for a sequence of size n and optimal cost OPT , any deterministic online algorithm requires at least $(n - 2 \text{OPT}) \log \text{OPT}$ bits of advice.*

Proof. Consider a class $S = \{\sigma_1, \dots, \sigma_N\}$ of sequences, so that each σ_r has length n ($1 \leq r \leq N$). Each sequence σ_r in the class has the form

$$\left\langle \frac{1}{4}, \frac{1}{8}, \frac{1}{16}, \dots, \frac{1}{2^{n-\text{OPT}+1}}, u_1^r, u_2^r, \dots, u_{\text{OPT}}^r \right\rangle$$

in which $u_1^r, \dots, u_{\text{OPT}}^r$ are defined as follows.:

Consider the set V of vectors of size $n - \text{OPT}$ that take values between 1 and OPT . More precisely, for a vector $V_r = (v_1^r, \dots, v_{n-\text{OPT}}^r) \in V$, we have $v_i^r \in \{1, \dots, \text{OPT}\}$. Also, assume that in each vector V_r the first occurrence of i in V_r is before that of $i + 1$ ($1 \leq i \leq n - \text{OPT} - 1$).

For example, when $n = 8$ and $\text{OPT} = 3$, the vector $(1, 2, 3, 2, 1)$ is in V , but $(1, 3, 2, 3, 1)$ is not.

We associate with each vector $V_r \in V$ a sequence $\sigma_r \in S$. For a vector $V_r \in V$ and bin j , define $u_j^r = 1 - \sum_{\substack{1 \leq i \leq n-\text{OPT} \\ v_i^r = j}} a_i$, where a_i is the i th item in the sequence σ_r , i.e.,

$a_i = \frac{1}{2^{i+1}}$. The sum over the empty set is defined to be 0. Note that all u_j s are strictly larger than .5. We refer to the first $n - \text{OPT}$ items as *small* items and the last OPT items as *large* items.

For example, assume $n = 8$ and $\text{OPT} = 3$. For a vector $V_r = (1, 2, 3, 2, 1)$, we have $u_1^r = 1 - (\frac{1}{4} + \frac{1}{64}) = .734375$, $u_2^r = 1 - (\frac{1}{8} + \frac{1}{32}) = .84375$, and $u_3^r = 1 - \frac{1}{16} = .9375$. Hence, the sequence σ_r associated with V_r is $\langle \frac{1}{4}, \frac{1}{8}, \frac{1}{16}, \frac{1}{32}, \frac{1}{64}, .734375, .84375, .9375 \rangle$.

In fact, V_r indicates in which bin each of the first $n - \text{OPT}$ items of σ_r should be placed, and at the end, u_j^r fills the empty space of the j th bin to capacity to achieve an

optimal packing P for a given sequence (it is optimal since all bins are fully packed). We claim that P is the unique optimal packing. Suppose there is another optimal packing P' . Observe that each bin includes at most one large item, and indeed exactly one since we assume it is also optimal. Let $a_i (1 \leq i \leq n - \text{OPT})$ be the first item which is placed in some other bin in P' than the one prescribed by P . Consider the bin B that a_i is placed into in P . This bin cannot be fully packed in P' since a_i is strictly larger than the total size of all remaining small items, i.e., even if we put all of them in the empty space of a_i , there is still some empty space in B . As a result P' cannot be optimal. Hence there is unique solution for packing each sequence of class S .

Note that there are $N = \text{OPT}^{n-\text{OPT}} / \text{OPT}!$ sequences in class S . We claim that these sequences need separate advice strings. Suppose otherwise, and let $\sigma_r, \sigma_{r'} \in S$ ($r \neq r'$) be two different sequences with the same advice string. Note that the first $n - \text{OPT}$ items in these sequences are the same. Since the online algorithm performs deterministically and we assume it receives the same advice for both σ_r and $\sigma_{r'}$, the partial packings of the algorithms after serving the first $n - \text{OPT}$ items are the same for both sequences. However, as discussed earlier, this implies that the final packing of the algorithm is different from the optimal packing prescribed by $V_{r''}$ for at least one of the sequences. As discussed, such a packing is the unique optimal packing and deviating from that increases the cost of the algorithm by at least one unit. As a result, the algorithm performs non-optimally for at least one of σ_r or $\sigma_{r'}$. We conclude that the sequences in class S need separate advice strings. Since there are $\text{OPT}^{n-\text{OPT}} / \text{OPT}!$ sequences in S , at least $\log(\text{OPT}^{n-\text{OPT}} / \text{OPT}!) = (n - \text{OPT}) \log(\text{OPT}) - \log(\text{OPT}!) \geq (n - 2 \text{OPT}) \log \text{OPT}$ bits of advice are required to get that many distinct advice strings. $\square$

2.2 A Practical Setting

A closer look at the proof of Theorem 2 reveals that we are building sequences having an unbounded number of distinct items, and the items are as small as $1/2^{n-\text{OPT}}$. In most practical settings, the number of distinct item sizes is not as large as n , and also the items are not arbitrarily small, i.e., there is a lower bound on the size of items that is independent of the value of n . In what follows, we consider a practical scenario where there are $m = o(n)$ distinct items and each item can be described using $\log m$ bits.

Lemma 1 ([12]). *Consider the restriction of the bin packing problem to instances in which the number of distinct item sizes is a constant non-negative integer m . There is a linear algorithm that optimally solves this restricted problem.*

In case there are more than a constant number of distinct items sizes, we can almost optimally solve the problem if the item sizes are lower bounded by a fixed value ε .

Lemma 2 ([22]). *Consider the restriction of the bin packing problem to instances in which each item is of size at least ε . There is a polynomial approximation algorithm that solves this restricted problem within a factor of $(1 + \varepsilon)$.*

Provided with the above lemmas, it is not hard to devise almost optimal online algorithms receiving $m \log n$ bits of advice.

Theorem 3. Consider the online bin packing problem under a practical setting in which there are m distinct items. If m is a constant, there is a (linear time) optimal online algorithm that receives $m \log n$ bits of advice. In case m is not a constant, but the items sizes are at least ε , there is a (polynomial time) optimal online algorithm that receives $m \log n$ bits of advice and achieves a competitive ratio of $1 + \varepsilon$.

Proof. The offline oracle simply encodes the input sequence, considered as a multi-set, in $m \log n$ bits of advice. In order to do that, it simply writes the number of occurrences of each of the m distinct items on the tape. The online algorithm uses the algorithms of Lemma 1 (for constant m) or Lemma 2 (for non-constant m) to compute an (almost) optimal packing, and packs the items in an online manner according to such a packing. $\square$

Thus, $m \log n$ bits of advice are sufficient for an online algorithm to (almost) optimally pack a sequence. We show that this bound is asymptotically tight by proving that at least $(m - 3) \log n - 2m \log m$ bits are required to achieve an optimal solution. Thus, for constant values of m , the lower and upper bounds are tight within lower order terms. To prove the theorem, we use the following simple lemma.

Lemma 3. Consider the equation $x_1 + 2x_2 + \dots + \alpha x_\alpha = X$ in which the x_i s ($i \leq \alpha$) and X are non-negative integers. If X is sufficiently large, then this equation has at least $\left(1 + \frac{2X}{\alpha(\alpha+1)}\right)^{\alpha-1}$ solutions.

Proof. Define $A = \sum_{i=1}^{\alpha} i$. Assign arbitrary values in the range $[0..X/A]$ to all x_i s for $2 \leq i \leq \alpha$ (for simplicity assume X/A is an integer). There are $(1 + X/A)^{\alpha-1}$ different such assignments. Any of these assignments defines a valid solution for the equation since by definition of A we have $\sum_{i=2}^{\alpha} i x_i \leq X$, and we can assign $x_1 = X - \sum_{i=2}^{\alpha} i x_i$. Replacing A with $\alpha(\alpha + 1)/2$ completes the proof. $\square$

Theorem 4. At least $(m - 3) \log n - 2m \log m$ bits of advice are required to achieve an optimal solution for the online bin packing problem on sequences of length n with m distinct items, each of size at least $\frac{1}{2m}$.

Proof. We define a family of sequences of length n and containing m distinct items and show that the sequences in this family need separate advice strings to be optimally served by an online algorithm. To define the family, we fix m item sizes as being $\{\frac{1}{2m}, \frac{m+2}{2m}, \frac{m+3}{2m}, \dots, \frac{2m-1}{2m}, 1\}$. To simplify the argument, we scale up the sizes of bins and items by a factor of $2m$. So, we assume the item sizes are $\{1, m+2, m+3, \dots, 2m-1, 2m\}$, and the bins have capacity $2m$. Each sequence in the family starts with $n/2$ items of size 1. Consider any packing of these items in which all bins have level at most equal to $m-2$. Such a packing includes a_1 bins of level 1 (one item in each), a_2 bins of level 2 (two items in each), etc., such that the a_i s are non-negative integers and $a_1 + 2a_2 + \dots + (m-2)a_{m-2} = n/2$. By Lemma 3, there are at least $\left(1 + \frac{n}{(m-1)(m-2)}\right)^{m-3}$ distinct packings with the desired property. For any of these packings, we define a sequence in our family. Such a sequence starts with $n/2$ items of size 1 and is followed by another $n/2$ items. Let B denote the number of bins in a

given packing of the first $n/2$ items, so that $B \leq n/2$. The sequence associated with the packing is followed by B items of size larger than $m + 1$ which completely *fit* these bins (in non-increasing order of their sizes). Finally, we include another $n/2 - B$ items of size $2m$ in the sequence to achieve a sequence of length n (see Figure 1).

We claim that any of the sequences in the family has a unique optimal packing of size $n/2$. This is because there are exactly $n/2$ *large* items of size strictly greater than m (more than half the capacity of the bin), and the other $n/2$ items have *small* size 1 (which fit the empty space of all bins). So each bin is fully packed with one large item of size x and $2m - x$ items of size 1.

The unique optimal packing of each sequence is defined by the partial packing of the first $n/2$ small items. Consider a deterministic online algorithm $\mathbb{A}$ receiving the same advice string for two sequence σ_1 and σ_2 . Since $\mathbb{A}$ is deterministic and both sequences start with the same sub-sequence of small items, the partial packing of the algorithm after packing the first $n/2$ items is the same for both σ_1 and σ_2 . As a result, the final packing of $\mathbb{A}$ is sub-optimal for at least one them. We conclude that any deterministic online algorithm should receive distinct advice strings for each sequence in the family. Since there are at least $\left(1 + \frac{n}{(m-1)(m-2)}\right)^{m-3}$ sequences in the family, at least $(m - 3) \log \left(1 + \frac{n}{(m-1)(m-2)}\right) > (m - 3) \log n - 2m \log m$ bits of advice are required. $\square$





Fig. 1. The optimal packings for two sequences of the family when $n = 30$ and $m = 6$ (item sizes and bin capacities are scaled by $2m = 12$).

3 An Algorithm with Sublinear Advice

In what follows we introduce an algorithm that receives $\log n$ bits of advice and achieves a competitive ratio of 1.5, for any instance of the online bin packing problem. An offline oracle can compute and write the advice on the tape in linear time, and the online algorithm runs as fast as First-Fit, i.e., in time $O(n \log \text{OPT})$. Thus, the algorithm might be applied in practical scenarios in which it is allowed to have a “quick look” at the input sequence. Recall that the competitive ratio 1.5 of the algorithm is strictly better than the ratio attainable by any online algorithm.

We call items *tiny*, *small*, *medium*, and *large* if their sizes lie in the intervals $(0, 1/3]$, $(1/3, 1/2]$, $(1/2, 2/3]$, and $(2/3, 1]$, respectively. The only advice that the algorithm receives is the number of medium items, which we denote by α .

The algorithm reads the advice tape, obtains α , and opens α bins, called *critical bins*, and reserves $2/3$ of the space in each of them. This reserved space will be used to place a medium item in each of the critical bins. These bins have a *virtual level* of size $2/3$ at the beginning. If a non-medium item is placed in such a critical bin, the virtual level is increased. When a medium item is placed in the reserved space, the virtual level is decreased to reflect the actual level. The algorithm serves an item x in the following manner:

- If x is a large item (has size larger than $2/3$), open a new bin for it.
- If x is a medium item, put it in the reserved space of a critical bin B . Update the virtual level to the actual level. (B will not have reserved space any more.)
- If x is small or tiny, use the FF strategy to put it into any of the open bins, based on virtual levels.

Theorem 5. *There is an online algorithm which receives $\log n$ bits of advice and has cost $3/2 \text{OPT}(\sigma) + 3$ for serving any sequence σ of size n .*

Proof. We prove that the algorithm described above has the desired property. Note that the algorithm receives $\log n$ bits of advice. Consider the final packing of the algorithm for serving a sequence σ . There are two cases. In the first case, there is a critical bin B so that no other item, except a medium item, is placed in it. Since all tiny items are smaller than $1/3$ and can fit in B , all the non-critical bins that are opened after B include small and large items only. More precisely, they include either a single large item or two small items (except the last one which might have a single small item). Let L , M , and S denote the number of large, medium, and small items. The cost of the algorithm is at most $L + M + S/2 + 1$. Now, if $S \leq M$, this would be at most $L + 3/2M + 1$. Since $L + M$ is a lower bound on the cost of OPT , the cost of the algorithm is at most $3/2 \text{OPT}(\sigma) + 1$ and we are done. If $S > M$, OPT should open $L + M$ bins for large and medium items, and in the best case, it packs M small items together with medium ones. For the other $S - M$ bins, OPT has to open at least $(S - M)/2$ bins. Hence the cost of OPT is at least $L + M + (S - M)/2 = L + M/2 + S/2$, and we have $3/2 \text{OPT}(\sigma) = 3L/2 + 3M/4 + 3S/4 > 3L/2 + M + S/2$. Thus, the cost of the algorithm is at most $3/2 \text{OPT}(\sigma) + 1$.

In the second case, we assume that all critical bins include another item in addition to the medium item. We claim that at the end of serving a sequence, all bins have level

at least $2/3$. First, we verify this for non-critical bins (bins without medium items). If a non-critical bin is opened by a large item, it clearly has level higher than $2/3$. All other non-critical bins only include items of size at most $1/2$. Hence, these bins, except possibly the last one, include at least two items. Consider two bins b_i and b_j ($i < j$) that have levels smaller than $2/3$. Since b_j contains at least two items, at least one of them has size smaller than $1/3$. That item could fit in b_i by the FF property. We conclude that all non-critical bins, except possibly one, have level at least $2/3$.

Now, suppose two critical bins b_i and b_j , excluding the last one, having levels smaller than $2/3$. Consider the first non-medium item x which is placed in b_j (in the second case, such an item exists). Since a medium item is placed in the bin, x should be either tiny or small. If x is small, then the level of b_j is at least $1/2 + 1/3$, which contradicts the level of b_j being smaller than $2/3$. Similarly, x cannot be a tiny item of size larger than $1/6$ (since $1/2 + 1/6 \geq 2/3$). Hence, x is a tiny item of size at most $1/6$. This implies that at the time the online algorithm places x , bin b_i has a virtual level of at least $5/6$. The virtual level is at most $1/3$ more than the actual level. Hence, the actual level of b_i is at least $5/6 - 1/3 = 2/3$. We conclude that at most two medium bins have level smaller than $2/3$. To summarize, at most 3 bins have level smaller than $2/3$. Hence, the cost of the algorithm is at most $3/2 \text{OPT}(\sigma) + 3$. $\square$

4 An Algorithm with Linear Advice

In this section, we present an algorithm that receives $2n + o(n)$ bits of advice and achieves a competitive ratio of $4/3 + \varepsilon$ for any sequence of size n , and arbitrarily small (but constant) values of ε .

Assume that the size of each item is approximated using k bits, so that the *approximate size* of the item is larger than its *actual size* by at most an additive term of $1/2^k$. We can receive the number of items of each approximate size in $2^k \log n$ bits of advice. The intuition is to optimally pack the items by their approximate sizes and achieve an *approximate packing*. For each item x , an approximate packing includes a reserved space of size $x + \varepsilon$ ($\varepsilon \leq 1/2^k$). This enables an online algorithm to pack any item in the reserved space for it in the approximate packing. So the cost of the online algorithm is equal to the number of bins in the approximate packing.

Unfortunately the cost of an approximate packing can be as large as 1.5 times the cost of OPT. To see that, consider a sequence which is permutation of a $.5 + \varepsilon_1, .5 - \varepsilon_1, .5 + \varepsilon_2, .5 - \varepsilon_2, \dots, .5 + \varepsilon_{n/2}, .5 + \varepsilon_{n/2}$, where $\varepsilon_i < 1/2^n$ ($1 \leq i \leq n/2$). Since OPT packs all bins tightly, an increase in the sizes of items by a constant small ε (which is necessary in the approximate packing) results in opening a new bin for each two bins of OPT. Hence the cost of the optimal approximate packing can be as bad as 1.5OPT .

The above example suggests that the approach of using approximate packings fails when there are bins in which a small number of large items are tightly packed. To provide a $4/3$ -competitive algorithm, we divide the bins of OPT into two groups:

Definition 2. Consider an optimal packing of a sequence σ . Given a small parameter $\varepsilon' < 1/60$, define good bins as those which include a subset of items, with total size of at most $1/4$, so that removing these items provides an empty space of size at least $5\varepsilon'$. Define all other bins to be bad bins.

A part of the advice received for each item x indicates if x is packed by OPT in a good bin or in a bad bin. This enables us to treat items packed in these two groups separately.

Lemma 4. *Consider sequences for which all bins in the optimal packing are good (as defined above). There is an online algorithm that receives $o(n)$ bits of advice in the beginning and achieves a competitive ratio of $4/3$.*

Proof. Call an item *small* if it is smaller than or equal to $1/6$ and *large* otherwise. The advice bits define the approximate sizes of all large items with a precision of ε' . The amount of advice will be roughly $2^{1/\varepsilon'} \log n$ which is $o(n)$ for constant values of ε' . The online algorithm $\mathbb{A}$ can build the optimal approximate packing of large items in polynomial time. In such a packing, there is a reserved space of size at most $x + \varepsilon'$ for any large item of size x . The algorithm considers this packing as a partial packing and initializes the level of each bin to be the total sizes of approximated items in that bin. For packing an item x , if x is large, $\mathbb{A}$ packs it in the space reserved for it in the approximate packing. It also updates the level of the bin to reflect the actual size of x . If x is small, $\mathbb{A}$ simply applies the First-Fit strategy to place x in a bin of the partial packing (and opens a new bin for it if necessary). We prove that $\mathbb{A}$ is $4/3$ -competitive. In the final packing by $\mathbb{A}$, call a bin “red” if all items packed in it are small items and call it “blue” otherwise (the blue bins constitute the approximated packing at the beginning). There are two cases to consider.

In the first case, there is no red bin in the final packing of $\mathbb{A}$, i.e., all small items fit in the remaining space of the bins in the approximate packing of large items. Let σ' be a copy of the input sequence in which the sizes of large items are approximated, i.e., increased by at most ε' ; also let X be the number of bins for the optimal packing of σ' . Since there is no red bin in the final packing of $\mathbb{A}$, the cost of $\mathbb{A}$ is equal to X . Consider the optimal packing of the actual input sequence σ . Since all bins are good, one can transfer a subset of items to provide an available space of size at least $5\varepsilon'$ in each bin. After such a transfer, we can increase the sizes of large items to their approximate sizes. Since there are at most 5 large items in each bin and also available space of size at least $5\varepsilon'$, the packing constructed this way is a valid packing for the sequence σ' . Since the size of the transferred items for each bin is at most $1/4$, and the transferred items from each group of four bins can fit in one new bin. Consequently the number of bins in the new packing is at most $5/4 \text{OPT}(\sigma)$. We know that the final packing by $\mathbb{A}$ is the optimal packing for σ' (with cost X), and in particular not worse than the packing constructed above. Hence, the cost of $\mathbb{A}$ is not more than $5/4 \text{OPT}(\sigma)$.

In the second case, there is at least one red bin in the final packing of $\mathbb{A}$. We claim that all bins in the final packing of $\mathbb{A}$, except possibly the last, have levels larger than $3/4$. The claim obviously holds for the red bins since the levels of all these bins (excluding the last one) are larger than $5/6$. Moreover, since there is a bin which is opened by a small item, all blue bins have levels larger than $5/6$, i.e., the total size of packed items and reserved space for the large items is larger than $5/6$. Since there are at most 5 large items in each bin, the actual level of each bin in the final packing of $\mathbb{A}$ is at least $5/6 - 5\varepsilon'$, which is not smaller than $3/4$ for $\varepsilon' \leq 1/60$. So, all bins, except possibly one, have levels larger than $3/4$. Consequently, the algorithm is $4/3$ -competitive. $\square$

It remains to address how to deal with bad bins. First, we prove two lemmas which are the basis of the our algorithm for packing items in bad bins.

Lemma 5. *Consider sequences for which all bins in the optimal packing include precisely two items. There is an algorithm that receives 1 bit of advice per request and achieves an optimal packing.*

Proof. The single bit of advice for an item x determines whether or not the *partner* of x appeared as a previous request, where the partner of x is the item which is packed in the same bin as x in OPT's packing. Consider an algorithm $\mathbb{A}$ that works as follows: If the partner of x has not been requested yet, $\mathbb{A}$ opens a new bin for x . Otherwise, it uses the BF strategy to pack x in one of the open bins. We claim that $\mathbb{A}$ achieves an optimal packing.

Assume that initially we have a mapping that maps the last item to go into a bin to the item it goes on top of in the optimal packing, i.e., it maps the second item of each bin to the first item. We update this mapping when necessary and maintain the invariant that we can always pack optimally according to the mapping. For serving a request x , if BF does not pack according to this mapping, it packs x on top of y' , while, according to the mapping, it was supposed to pack x on top of y , and a later x' is supposed to go on top of y' . Due to the BF strategy, $y' \geq y$, so we can update the mapping to map the currently unprocessed x' to y , and, of course, x to y' . $\square$

Lemma 6. *Consider a sequence σ for which all items have sizes larger than $1/4$ and for which each bin in OPT's packing includes precisely three items. The cost of the Harmonic algorithm is at most $4/3 \text{OPT}(\sigma) + 3$ for serving such a sequence.*

Proof. The proof is based on a simple weighting function. Call an item x *large* if $1/3 < x < 1/2$ and *small* otherwise ($1/4 < x \leq 1/3$). Define the weight of x to be $1/2$ if x is large and $1/3$ if it is small. Consider a bin B in the packing of σ by OPT. Since there are three items in B , its weight is maximized when there are two large items and one small item in it (three large item do not fit in the same bin). Hence, the weight of each bin in the OPT packing is at most $2 \times 1/2 + 1/3 = 4/3$. Consequently, we have $\text{OPT}(\sigma) \geq 3/4W$, where W is the total weights of all items.

The Harmonic algorithm (HA) simply packs small and large items in separate collections of bins. So, each of the algorithm's bins, except possibly two bins, contains either three small items or two large items. In both cases, the weight of each bin is at least 1 and we have $\text{HA}(\sigma) \leq W + 2$. As a conclusion $\text{HA}(\sigma) \leq 4/3 \text{OPT}(\sigma) + 2$ which completes the proof. $\square$

Lemma 7. *Consider a sequence σ for which all bins in the optimal packing are bad bins (as defined earlier). There is an algorithm that receives two bits of advice for each request, and opens at most $(4/3 + \frac{5\varepsilon'}{1-5\varepsilon'}) \text{OPT}(\sigma) + 3$ bins.*

Proof. By the definition of bad bins, for any bin in the optimal packing, there is no subset of items whose removal provides an available space of size in the range $[5\varepsilon', 1/4]$. So, all items are either smaller than $5\varepsilon'$ or larger than $1/4$. We call the former group of items *tiny* items and pack them separately using the FF strategy. We refer to other items as *normal* items. Consider an offline packing OPT' which is the same as OPT, except

that all tiny items are removed from their bins and packed separately in new bins using the FF strategy. This implies that the cost of OPT' is more than OPT by a multiplicative factor of at most $1 + \frac{5\varepsilon'}{1-5\varepsilon'}$. In OPT' 's packing, consider the bins with normal items. Since all items are larger than $1/4$, each bin contains at most three items. We say a bin of OPT' has type i ($i \in \{1, 2, 3\}$), if it contains i normal items. Similarly, we say an item x has type i if it is packed in a type i bin. All items in type 3 bins have sizes smaller than $1/2$ (otherwise one will have size at most $1/4$ which contradicts the assumption). Moreover, the sizes of the items in all type 1 bins (except possibly the last one) are larger than $1/2$ (otherwise a better packing is achieved by pairing two of them). We conclude that with two bits of advice, we can detect the type of an item. To be more precise, let b denote the two bits of advice with item x . If b is "01" and $x > 1/2$, then x has type 1; if b is "01" and $x \leq 1/2$, then x has type 3; and if b is "10" or b is "11", then x has type 2. Note that the code "00" is not used, and the use of "10" and "11" is still to be detailed.

Let X_i denote the number of bins of type i ($1 \leq i \leq 3$). Hence, we have $\text{OPT}' = X_1 + X_2 + X_3 + X'$, where X' is the number of bins filled by tiny items. Consider an algorithm $\mathbb{A}$ that performs as follows. If an item x has type 1, $\mathbb{A}$ simply opens a new bin for x . If x has type 2, the algorithm applies the strategy in Lemma 5 to pack these items in X_2 bins. Recall that the advice in this case is either "10" or "11", so the second bit provides the advice required by Lemma 5. The cost of the algorithm for packing the items of types 1 and 2 is $X_1 + X_2$. If x has type 3, $\mathbb{A}$ applies the Harmonic strategy to pack the item in a set of bins maintained for type 3 items. By Lemma 6, the cost of the algorithm for these items is at most $4/3X_3 + 2$. Finally, $\mathbb{A}$ simply uses the FF strategy to pack tiny items in separate bins. Consequently, the cost of the algorithm for serving all items is $X_1 + X_2 + 4/3X_3 + X' + 2 \leq (4/3 + \frac{5\varepsilon'}{1-5\varepsilon'}) \times \text{OPT} + 3$. $\square$

Provided with the above results, we arrive at the following result:

Theorem 6. *There is an online algorithm which receives two bits of advice per request, and achieves a competitive ratio of $4/3 + \varepsilon$, for any positive value of $\varepsilon < 1/11$.*

Proof. Define ε' to be $\frac{11\varepsilon}{60}$. Note that since $\varepsilon < 1/11$, we have $\varepsilon' < 1/60$. Moreover, we have $\frac{5\varepsilon'}{1-5\varepsilon'} \leq \frac{5\varepsilon'}{1-1/12} = \frac{60\varepsilon'}{11} = \varepsilon$. In an optimal packing, divide bins into good and bad bins using Definition 2. Also, let Gd and Bd respectively denote the number of good and bad bins. Use advice bits to distinguish items which are packed in good and bad bins, and pack them in separate lists of bins. More precisely, let the two bits of advice for an item x be "00" if it is packed by OPT in a good bin, and apply Lemma 4 to pack items these items in at most $4/3Gd$ bins. Similarly, apply Lemma 7 to pack items from bad bins in at most $(4/3 + \frac{5\varepsilon'}{1-5\varepsilon'})Bd + 3 \leq (4/3 + \varepsilon)Bd + 3$ bins, using bits of advice of the form "01", "10", or "11", as discussed in the proof of Lemma 7. Consequently, the cost of the algorithm will be at most $4/3Gd + (4/3 + \varepsilon)Bd + 3 \leq (4/3 + \varepsilon)\text{OPT}(\sigma) + 3$. $\square$

5 A Lower Bound for Linear Advice

In this section we show that an online algorithm needs a linear number of bits of advice to achieve a competitive ratio better than $5/4$. We make use of the *Binary String Guessing Problem*, which is defined and analyzed in [4].

Definition 3 ([4]). *The Binary String Guessing Problem with known history (2-SGKH) is the following online problem. The input $I = (n, x_1, x_2, \dots, x_n)$ consists of n items that are either 0 or 1 and that are revealed one by one. For each item x_t , the online algorithm $\mathbb{A}$ must guess if it is a 0 or a 1. After the algorithm has made a guess, the value of x_t is revealed to the algorithm.*

Lemma 8 ([4]). *On input of length n , any deterministic algorithm for 2-SGKH that is guaranteed to guess correctly on more than αn bits, for $1/2 \leq \alpha < 1$, needs to read at least $(1 + (1 - \alpha) \log(1 - \alpha) + \alpha \log \alpha)n$ bits of advice.*

Since the number of bits needed to express the number of “0”s in the input is at most $\log n$, and this number can be given as advice by an oracle, if it is not given to the algorithm otherwise, we easily obtain the following:

Lemma 9. *Consider instances of size n of the 2-SGKH problem in which the number of “0”s is given to the algorithm as part of the input. For these instances, any deterministic algorithm that is guaranteed to guess correctly on more than αn bits, for $1/2 \leq \alpha < 1$, needs to read at least $(1 + (1 - \alpha) \log(1 - \alpha) + \alpha \log \alpha)n - 2(\log n + 2)$ bits of advice.*

Proof. Assume to the contrary that the statement is not true. Hence, there is an algorithm, BSGA, that knows the number of “0”s and receives fewer than $(1 + (1 - \alpha) \log(1 - \alpha) + \alpha \log \alpha)n - 2(\log n + 2)$ bits of advice while guessing correctly on more than αn bits. This algorithm can be used to serve arbitrary instances of the 2-SGKH problem (in which the number of “0”s is not known). Modify the advice tape used by the algorithm BSGA so that it contains at most $2(\log n + 2)$ additional bits at the beginning specifying the number of “0”s. (The number can for instance be encoded using two zeros for each zero, two ones for each one, and the pattern “10” to signal the end of the encoding.) The algorithm for 2-SGKH reads this number and gives it to BSGA. Then it asks BSGA for its guess for each bit in the sequence and answers the same as BSGA. It also informs BSGA of when it is correct and when it is wrong, with the same information it is given. The algorithm is correct exactly when BSGA is correct. The total number of advice bits will be less than $2(\log n + 2) + (1 + (1 - \alpha) \log(1 - \alpha) + \alpha \log \alpha)n - 2(\log n + 2) = (1 + (1 - \alpha) \log(1 - \alpha) + \alpha \log \alpha)n$. However, Lemma 8 implies that no algorithm can guess correctly on more than αn bits with this many bits of advice. In conclusion, the initial assumption is incorrect and the statement holds. $\square$

In order to relate the Binary String Guessing Problem to the online bin packing problem, we introduce another problem called the Binary Separation Problem.

Definition 4. *The Binary Separation Problem is the following online problem. The input $I = (n_1, y_0, y_1, \dots, y_n)$ consists of $n = n_1 + n_2$ positive values which are revealed one by one. There is a fixed partitioning of the set of items into a subset of n_1 large items*

and a subset of n_2 small items, so that all large items are larger than all small items. Upon receiving an item y_i , an online algorithm for the problem must guess if y belongs to the set of small or large items. After the algorithm has made a guess, it is revealed to the algorithm whether y_i actually belongs to class of small or large items.

We provide reductions from the modified Binary String Guessing Problem to the Binary Separation Problem, and from the Binary Separation Problem to the online bin packing problem. In order to reduce a problem P_1 to another problem P_2 , given an instance of P_1 defined by a sequence σ_1 and a set of parameters η_1 (such as the length of σ_1 or the number of “0”s in it), we create an instance of P_2 which is defined by a sequence σ_2 and also a set of parameters η_2 . In our reductions, we assume η_2 is derived from η_1 , and since σ_1 is revealed in an online manner, σ_2 is created in an online manner by looking only at η_1 and the revealed items of σ_1 .

Lemma 10. *Assume that there is an online algorithm that solves the Binary Separation Problem on sequences of length n with $b(n)$ bits of advice, and makes at most $r(n)$ mistakes. Then there is also an algorithm that solves the Binary String Guessing Problem on sequences of length n , assuming the number of “0”s is given as a part of input, so that the algorithm receives $b(n)$ bits of advice and makes at most $r(n)$ errors.*

Proof. We assume that we have an algorithm BSA that solves the Binary Separation Problem under the conditions of the lemma statement. Using that algorithm, we define the number n_1 of large items to be the number of “0”s in the instance of the Binary String Guessing Problem. Then, we implement our algorithm BSGA for the Binary String Guessing Problem as outlined in Algorithm 1, which defines the reduction.

Note that this BSGA implementation, defined in Algorithm 1, functions as an adversary for BSA, e.g., in Line 5, BSGA gives BSA its next request. Notice that we ensure that the BSGA makes a correct guess if and only if BSA makes a correct guess. The advice tape is filled with bits of advice for this combined algorithm. The BSGA uses the BSA as a sub-routine, but all the questions are effectively coming from the BSA.

The set-up, reminiscent of binary search, is carried out as specified in the algorithm with the purpose of ensuring that when the BSA is informed of the actual class of the item it considered, no result can contradict information already obtained. Specifically, the next item for the BSA to consider is always in between the largest item which has previously been deemed “small” and the smallest item which has previously been deemed “large”. The fact that we give the middle item from that interval is unimportant; any value chosen from the open interval would work. $\square$

Now, we prove that if we can solve a special case of the bin packing problem, we can also solve the Binary Separation Problem.

Lemma 11. *Consider the bin packing problem on sequences of length $2n$ for which OPT opens n bins. Assume that there is an online algorithm $\mathbb{A}$ that solves the problem on these instances with $b(n)$ bits of advice and opens at most $n + r(n)/2$ bins. Then there is also an algorithm BSA that solves the Binary Separation Problem on sequences of length n with $b(n)$ bits of advice and makes at most $r(n)$ errors.*

Algorithm 1 Implementing Binary String Guessing via Binary Separation.

```
1: small = 0
2: large = 1
3: repeat
4:   mid = (large - small) / 2
5:   class_guess = SeparationAlgorithm.ClassifyThis(mid)
6:   if class_guess = "large" then
7:     bit_guess = 0
8:   else
9:     bit_guess = 1
10:  actual_bit = Guess(bit_guess) {The actual value is received after guessing (2-SGKH).}
11:  if actual_bit = 0 then
12:    large = mid {We let "large" be the correct decision.}
13:  else
14:    small = mid {We let "small" be the correct decision.}
15: until end of sequence
```

Proof. In the reduction, we encode requests for the BSA as items for bin packing. Assume we are given an instance $I = (n_1, y_0, y_1, \dots, y_n)$ of the Binary Separation problem, in which n_1 is the number of large items ($n_1 + n_2 = n$), and the values of y_t s are revealed in an online manner ($1 \leq t \leq n$). We create an instance of the bin packing problem which has length $2n$. Algorithm 2 shows the details of the reduction. The bin packing sequence starts with n_1 items of size $.5 + \epsilon_{min}$ (in Algorithm 2, the variable "NumberOfLargeItems" is n_1 from the Binary Separation Problem). Note that any algorithm needs to open a bin for each of these n_1 items. We create the next n items in an online manner, so that we can use the result of their packing to guess the requests for the Binary Separation Problem. Let $\tau = y_t$ ($1 \leq t \leq n$) be a requested item of the Binary Separation Problem; we ask the bin packing algorithm to place an item whose size is an increasing function of τ , and slightly less than $.5$. Depending on the decision of the bin packing algorithm for opening a new bin or placing the item in one of the existing bins, we decide the type of τ as being consecutively small or large. The last n_2 items of the bin packing instance are defined as complements of the items in the bin packing instance associated with small items in the binary separation instance (the complement of item x is $1 - x$). We do not need to give the last items complementing the small items in order to implement the algorithm, but we need them for the proof of the quality of the correspondence that we are proving.

Call an item in the bin packing sequence "large" if it is associated with large items in the Binary Separation Problem, and "small" otherwise. For the bin packing sequence produced by the reduction, an optimal algorithm pairs each of the large items with one of the first n_1 items (those with size $.5 + \epsilon_{min}$), placing them in the first n_1 bins. OPT pairs the small items with their complements, starting one of the next n_2 bins with each of these small items. Hence, the cost of an optimal algorithm is $n_1 + n_2 = n$.

The values ϵ_{min} and ϵ_{max} in Algorithm 2 must be small enough so that no more than two of any of the items given in the algorithm can fit together in a bin. No other restriction is necessary.

Algorithm 2 Implementing Binary Separation via Special Case Bin Packing.

```
1: Choose  $\varepsilon_{min}$  and  $\varepsilon_{max}$  so that  $0 < \varepsilon_{min} < \varepsilon_{max} < \frac{1}{6}$ 
2: Choose a decreasing function  $f: \mathbb{R} \rightarrow (\varepsilon_{min}.. \varepsilon_{max})$ 
3: for  $i = 1$  to NumberOfLargeItems do
4:   BinPacking.Treat( $.5 + \varepsilon_{min}$ ) {The decision can only be to open a bin.}
5: repeat
6:   Let  $\tau$  be the next request
7:   decision = BinPacking.Treat( $.5 - f(\tau)$ )
8:   if decision = “packed with an  $.5 + \varepsilon_{min}$  item” then
9:     class_guess = “large”
10:  else
11:    class_guess = “small”
12:    actual_class = Guess(class_guess)
13:    if actual_class = “small” then
14:      SmallItems.append( $\tau$ ) {Collecting small items for later.}
15: until end of request sequence
16: for  $i = 1$  to len(SmallItems) do
17:   BinPacking.Treat( $1 - \text{SmallItems}[i]$ ) {The decision is not used.}
```

We claim that each extra bin used by the bin packing algorithm, but not by OPT, results in at most two mistakes made by the derived algorithm on the given instance of the Binary Separation Problem. Note that a deviation from the optimal packing happens when $\mathbb{A}$ opens a new bin for a large item or $\mathbb{A}$ places a small item in an existing bin. If $\mathbb{A}$ opens a new bin for a large item, in the final packing of $\mathbb{A}$, there is an extra bin compared to the optimal packing. This is because large items do not fit in the same bins as complements of small items. The extra bin has enough space for another large item, hence, there is an overhead of one for two mistakes. Similarly, if $\mathbb{A}$ packs a small item with one of the first n_l items, it eventually has to open a new bin for a large item (since there are only n_l spots in the bins of the first n_l bins which should be reserved for large items). To summarize, $\mathbb{A}$ has to decide if a given item is small or large and performs accordingly, and it pays a cost of at least $1/2$ for each incorrect decision. If $\mathbb{A}$ opens at most $n + r(n)/2$ bins, since there are at most two items in each bin, it has deviated from optimal packings for at most $r(n)$ items, and, consequently, the algorithm derived from $\mathbb{A}$ for the Binary Separation Problem makes at most $r(n)$ mistakes. $\square$

Based on the above results, we prove the following theorem:

Theorem 7. *Consider the online bin packing problem on sequences of length n . To achieve a competitive ratio of c ($1 < c \leq 5/4$), an online algorithm needs to receive at least $(n(1 + (2c - 2) \log(2c - 2) + (3 - 2c) \log(3 - 2c)) - 2(\log n + 2))/2$ bits of advice.*

Proof. Consider a bin packing algorithm $\mathbb{A}$ that receives $b(n)$ bits of advice and achieves a competitive ratio of c . This algorithm opens at most $(c - 1)$ OPT bins more than OPT, so when $\text{OPT} = n/2$, it opens $(c - 1)n/2$ bins. By Lemma 11, the existence of such an algorithm implies that there is an algorithm $\mathbb{A}$ that solves the Binary Separation Problem on sequences of length $n/2$ with b bits of advice and makes at most

$(c - 1)n$ errors. By Lemma 10, this implies that there is an algorithm $\mathbb{B}$ that solves the Binary String Guessing Problem on sequences of length $n/2$ with b bits of advice and makes at most $(c - 1)n$ mistakes, i.e., it correctly guesses the other $n/2 - (c - 1)n = (3 - 2c)n/2$ items. Let $\alpha = 3 - 2c$, and note that α is in the range $[1/2, 1)$ when c is in the range $(1, 5/4]$. Lemma 9 implies that in order to correctly guess more than $\alpha n/2$ of the items in the binary sequence, we must have $b(n)$ larger than or equal to $((1 + (1 - \alpha) \log(1 - \alpha) + \alpha \log \alpha)n - 2(\log n + 2))/2$. Replacing α with $3 - 2c$ completes the proof. $\square$

For a competitive ratio of $5/4$, Theorem 7 does not say anything stronger than that zero bits of advice are required. However for doing better than $5/4$, a linear number of bits of advice is required. For example, to achieve a competitive ratio of $9/8$, at least $n/10$ bits of advice are required.

Corollary 1 *Consider the bin packing problem for packing sequences of length n . To achieve a competitive ratio of $5/4 - \delta$, in which δ is a small, but fixed positive number, an online algorithm needs to receive $\Omega(n)$ bits of advice.*

6 Concluding Remarks

We conjecture that a sublinear number of bits of advice is enough to achieve competitive ratios smaller than $4/3$. Note that our results imply that we cannot hope for ratios smaller than $5/4$ with sublinear advice. Another direction for future work is studying the extension of the bin packing problem to higher dimensions under the advice model of complexity. We suggest that methods used in this paper could be applied to provide algorithms as well as lower bounds for multi-dimensional bin packing.

References

1. E. Asgeirsson, U. Ayesta, E. Coffman, J. Etra, P. Momcilovic, D. Phillips, V. Vokhshoori, Z. Wang, and J. Wolfe. Closed on-line bin packing. *Acta Cybern.*, 15(3):361–367, September 2002.
2. J. Baewicz and K. Ecker. A linear time algorithm for restricted bin packing and scheduling problems. *Operations Research letters*, 2(2):80–83, 1983.
3. János Balogh, József Békési, and Gábor Galambos. New lower bounds for certain classes of bin packing algorithms. *Theoretical Computer Science*, 440–441:1–13, 2012.
4. Hans-Joachim Böckenhauer, Juraj Hromkovič, Dennis Komm, Sacha Krug, Jasmin Smula, and Andreas Sprock. The string guessing problem as a method to prove lower bounds on the advice complexity. In *Electronic Colloquium on Computational Complexity*, ECCC, 2012.
5. Hans-Joachim Böckenhauer, Dennis Komm, Rastislav Kráľovič, and Richard Kráľovič. On the advice complexity of the k -server problem. In *Proceedings of the 38th international colloquium conference on Automata, languages and programming - Volume Part I, ICALP'11*, pages 207–218, Berlin, Heidelberg, 2011. Springer-Verlag.
6. Hans-Joachim Böckenhauer, Dennis Komm, Rastislav Kráľovič, Richard Kráľovič, and Tobias Mömke. On the advice complexity of online problems. In *Proceedings of the 20th International Symposium on Algorithms and Computation, ISAAC '09*, pages 331–340, 2009.

7. Hans-Joachim Böckenhauer, Dennis Komm, Richard Kráľovič, and Peter Rossmanith. On the advice complexity of the knapsack problem. In *Proceedings of the 10th Latin American international conference on Theoretical Informatics*, LATIN'12, pages 61–72, 2012.
8. Edward G. Coffman, Jr., Michael R. Garey, and David S. Johnson. Approximation algorithms for bin packing: a survey. *Approximation algorithms for NP-hard problems*, pages 46–93, 1997.
9. Stefan Dobrev, Rastislav Kráľovic, and Euripides Markou. Online graph exploration with advice. In *Proceedings of the 19th International Colloquium on Structural Information and Communication Complexity*, SIROCCO'12, pages 267–278, 2012.
10. Stefan Dobrev, Rastislav Kráľovič, and Dana Pardubská. How much information about the future is needed? In *Proceedings of the 34th conference on Current trends in theory and practice of computer science*, SOFSEM'08, pages 247–258, Berlin, Heidelberg, 2008. Springer-Verlag.
11. Yuval Emek, Pierre Fraigniaud, Amos Korman, and Adi Rosén. Online computation with advice. In *Proceedings of the 36th International Colloquium on Automata, Languages and Programming: Part I*, ICALP '09, pages 427–438, 2009.
12. Michal Forišek, Lucia Keller, and Monika Steinová. Advice complexity of online coloring for paths. In *Proceedings of the 6th international conference on Language and Automata Theory and Applications*, LATA'12, pages 228–239, 2012.
13. P. R. Freeman. The secretary problem and its extensions: a review. *International Statistical Review*, 51(2):189–206, 1983.
14. Edward F. Grove. Online bin packing with lookahead. In *Proceedings of the sixth annual ACM-SIAM symposium on Discrete algorithms*, SODA '95, pages 430–436, Philadelphia, PA, USA, 1995. Society for Industrial and Applied Mathematics.
15. Joachim Gudmundsson, Julián Mestre, and Taso Viglas, editors. *Computing and Combinatorics - 18th Annual International Conference, COCOON 2012, Sydney, Australia, August 20-22, 2012. Proceedings*, volume 7434 of *Lecture Notes in Computer Science*. Springer, 2012.
16. Juraj Hromkovič, Rastislav Kráľovič, and Richard Kráľovič. Information complexity of online problems. In *Proceedings of the 35th international conference on Mathematical foundations of computer science*, MFCS'10, pages 24–36, 2010.
17. Anna R. Karlin, Mark S. Manasse, Lyle A. McGeoch, and Susan Owicki. Competitive randomized algorithms for non-uniform problems. In *Proceedings of the first annual ACM-SIAM symposium on Discrete algorithms*, SODA '90, pages 301–309, Philadelphia, PA, USA, 1990. Society for Industrial and Applied Mathematics.
18. Dennis Komm, Richard Kráľovic, and Tobias Mömke. On the advice complexity of the set cover problem. In *CSR*, pages 241–252, 2012.
19. Dennis Komm and Richard Kráľovič. Advice complexity and barely random algorithms. In *Proceedings of the 37th international conference on Current trends in theory and practice of computer science*, SOFSEM'11, pages 332–343, 2011.
20. Marc P. Renault and Adi Rosén. On online algorithms with advice for the k-server problem. In *Proceedings of the 9th international conference on Approximation and Online Algorithms*, WAOA'11, pages 198–210, 2012.
21. Steven S. Seiden. On the online bin packing problem. *J. ACM*, 49:640–671, September 2002.
22. Vijay V. Vazirani. *Approximation Algorithms*. Springer, 2004.